Page: 1 of 5 Printed: 01/12/2023 Revision: 01/11/2023

Supersedes Revision: 07/21/2020

This SDS complies with the Canadian Hazardous Products Regulations of 2015.

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Klean-Strip Boiled Linseed Oil

Reference #: 1660C Company Name: W. M. Barr

> 2105 Channel Avenue Memphis, TN 38113

Web site address: www.wmbarr.com

Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346

Information: W.M. Barr Customer Service (800)398-3892

Intended Use: Paint Thinner

Product Code: GLO45, QLO45, CLO45, GKLO145, QKLO146

2. HAZARDS IDENTIFICATION

GHS Signal Word: None

GHS Hazard Phrases:

GHS Precautionary Phrases: GHS Response Phrases: GHS Storage and Disposal

Phrases:

OSHA Regulatory Status: This material is classified as not hazardous under OSHA regulations.

Medical Conditions Generally None known.

Aggravated By Exposure:

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS # Hazardous Components (Chemical Name) Concentration

68553-15-1 Linseed oil, cobalt manganese salt {Linseed oil, $\,$ 80.0 -100.0 %

manganese and cobalt driers}

4. FIRST AID MEASURES

Emergency and First Aid INHALATION:

Procedures: If user experiences breathing difficulty, move to fresh air. If not breathing, give artificial

respiration. If breathing is difficult, give oxygen. Get medical attention.

SKIN CONTACT:

wash with soap and water.

EYE CONTACT:

Flush eye with water for at least 15 minutes. Get immediate medical attention.

INGESTION:

Call your poison control center, hospital emergency room, or physician immediately for

instructions.

Signs and Symptoms Of

. .

Exposure:

See Potential Health Effects.

Licensed to W.M. Barr and Company: MIRS SDS, (c) A V Systems, Inc.

Multi-region format

Page: 2 of 5 Printed: 01/12/2023 Revision: 01/11/2023

Supersedes Revision: 07/21/2020

5. FIRE FIGHTING MEASURES

Flammability Classification: IIIB

Flash Pt: 98.9 C (210.00 F)

Explosive Limits: LEL: UEL:

Autoignition Pt: > 343.9 C (> 651.00 F)

Suitable Extinguishing Media: Use carbon dioxide, dry powder, or foam.

Fire Fighting Instructions: Self-contained respiratory protection should be provided for fire fighters fighting fires in

buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have

been exposed to intense heat or flame.

Flammable Properties and

Hazards:

RISK OF FIRE FROM SPONTANEOUS COMBUSTION EXISTS WITH THIS

PRODUCT.

Oily rags, waste, and other oily materials can cause spontaneous combustion fires if not handled properly. Immediately after use, and before disposal or storage, you MUST (1) Spread out all oily materials outside to dry by flattening them out to their full size in an airy spot for 24 hours at temperatures above 40 degrees F, or (2) Wash them thoroughly with water and detergent and rinse. Repeat until you have removed all oil from all clothes, tools, rags, paper, clothing, mops, and any other materials contacted during use or as a result of an accidental spill. Make certain all wash and rinse water is disposed of

properly.

Hazardous Combustion

Products:

Carbon monoxide and carbon dioxide.

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled: Keep unneccessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut of ignition sources; keep flares, smoking or flames out of hazard area.

Small Spills: take up liquid with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.

Large Spills: dike far ahead of spill for later disposal.

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Precautions To Be Taken in

Storing:

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS # Chemical Name Jurisdiction Recommended Exposure Limits Notations
68553-15-1 Linseed oil, cobalt ACGIH TLV TWA: 0.02 mg/m3 (resp.) 0.1 mg/m3 (IHL)

manganese salt {Linseed oil, manganese and cobalt driers}

OSHA PELs CEIL: 5 mg/m3

Recommended Exposure vegetable oil mist

Licensed to W.M. Barr and Company: MIRS SDS, (c) A V Systems, Inc.

Multi-region format

Page: 3 of 5
Printed: 01/12/2023
Revision: 01/11/2023

Supersedes Revision: 07/21/2020

Limits: ACGIH: TLV: 10 mg/m3

OSHA PEL - TWA: 15 mg/m3, TWA: 5 mg/m3

Respiratory Equipment

(Specify Type):

For occasional consumer use - Use with adequate ventilation to prevent a build-up of vapors in confined areas. Open windows or position fans to provide cross ventilation. If

a mild to strong odor is noticeable, ventilation is not adequate.

For OSHA controlled workplace and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding

appropriate TLVs.

For occasional use, where engineered air control is not feasible, use properly maintained

and properly fitted NIOSH approved respirators. A dust mask does not provide

protection against vapors.

Eye Protection: Safety glasses, chemical goggles, or face shields are recommended to safeguard

against potential eye contact, irritation, or injury. Contact lenses should not be worn

while working with chemicals.

Protective Gloves: Wear impermeable gloves. Gloves contaminated with product should be discarded.

Follow disposal procedures as described in Section 5 and Section 7.

Other Protective Clothing: Various application methods can dictate use of additional protective safety equipment,

such as impermeable aprons, etc., to minimize exposure.

Engineering Controls (Ventilation etc.):

Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- STOP -- ventilation is inadequate. Leave area immediately

and move to fresh air.

Work/Hygienic/Maintenance

Practices:

A source of clean water should be available in the work area for flushing of eyes and

skin.

Clothing that becomes soiled with product should be removed as soon as possible and laundered separately. Follow procedures outlined in Section 7, Handling and Storage.

Wash hands thoroughly after use and before eating, drinking, or smoking.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States: [] Gas [X] Liquid [] Solid

Appearance and Odor: Clear Amber

pH:

Melting Point: Boiling Point:

Flash Pt: 98.9 C (210.00 F)

Evaporation Rate:

Flammability (solid, gas):

Explosive Limits: LEL: UEL:

Vapor Pressure (vs. Air or

mm Hg):

Vapor Density (vs. Air = 1):

Specific Gravity (Water = 0.93 at 25.0 C (77.0 F)

1):

Licensed to W.M. Barr and Company: MIRS SDS, (c) A V Systems, Inc.

Page: 4 of 5 Printed: 01/12/2023 Revision: 01/11/2023

Supersedes Revision: 07/21/2020

So	lubi	lity	in	W	ate	1
Sat	tura	ted	Va	р	or	

Concentration:

Octanol/Water Partition

Coefficient:

Autoignition Pt:

> 343.9 C (> 651.00 F)

Decomposition Temperature:

Viscosity:

Information with regard to primary physical hazard:

10. STABILITY AND REACTIVITY

Unstable [] Stable [X] Stability:

Conditions To Avoid -

Instability:

Incompatibility - Materials To Incompatible with strong oxidizing agents.

Hazardous Decomposition or Decomposition may produce carbon monoxide and carbon dioxide.

Byproducts:

Possibility of Hazardous

Will occur [] Will not occur [X]

Reactions:

Conditions To Avoid -Hazardous Reactions:

11. TOXICOLOGICAL INFORMATION

Toxicological Information: Refer to section 2 for acute and chronic effects.

CAS# 68553-15-1:

Standard Draize Test, Skin, Human, 300.0 MG, 3 D, Moderate.

Result:

Sense Organs and Special Senses (Nose, Eye, Ear, and Taste): Ear: Changes in

cochlear structure or function.

Nutritional and Gross Metabolic: Weight loss or decreased weight gain.

- Cutaneous Toxicity, Proceedings of the 3rd Conference, 1976, D, V.A., and P. L, New

IARC

ACGIH

NTP

York, Academic Press, Inc., London United Kingdom, Vol/p/yr: -,127, 1977

CAS# **Hazardous Components (Chemical Name)**

Linseed oil, cobalt manganese salt {Linseed oil,

manganese and cobalt driers}

12. ECOLOGICAL INFORMATION

This product has not been tested as a whole. General Ecological

Information:

68553-15-1

Licensed to W.M. Barr and Company: MIRS SDS, (c) A V Systems, Inc.

OSHA

Page: 5 of 5
Printed: 01/12/2023
Revision: 01/11/2023

Supersedes Revision: 07/21/2020

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose in accordance with applicable local, state, and federal regulations.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Not Regulated by 49 CFR

DOT Hazard Class: UN/NA Number:

LAND TRANSPORT (Canadian TDG):

TDG Shipping Name: Not Regulated by 49 CFR

UN Number: Hazard Class:

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS # Hazardous Components (Chemical Name) S. 302 (EHS) S. 304 RQ S. 313 (TRI)

68553-15-1 Linseed oil, cobalt manganese salt {Linseed oil, No No Yes-Cat. N096, N450

manganese and cobalt driers}

CAS # Hazardous Components (Chemical Name) Canadian NPRI Canadian Toxic Canadian DSL

68553-15-1 Linseed oil, cobalt manganese salt {Linseed oil, Yes - Cat.

manganese and cobalt driers}

CAS # Hazardous Components (Chemical Name) Other US EPA or State Lists

68553-15-1 Linseed oil, cobalt manganese salt {Linseed oil, CAA HAP,ODC: Yes - Cat.

manganese and cobalt driers}

TSCA: Inventory

Additional Regulatory

Information

This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

TDG Classification:

16. OTHER INFORMATION

Revision Date: 01/11/2023 **Previous revision:** 07/21/2020

Preparer Name: W.M. Barr EHS Dept (901)775-0100

Additional Information About

This Product:

Company Policy or

Disclaimer:

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

Licensed to W.M. Barr and Company: MIRS SDS, (c) A V Systems, Inc.

Multi-region format